TRAFFIC LAW ENFORCEMENT SYSTEM

Background of the Invention:

This is a continuation-in-part application of PCT application No. PCT/US97/18871, filed 28 October 1997, the contents of which are incorporated herein by reference

This invention relates to traffic enforcement devices for use in enforcing traffic ordinances More specifically, this invention relates to remotely operated enforcement systems having velocity determining and recording means.

In the United States, the prevalent method of enforcing traffic laws is to utilize police officers who patrol the streets in police patrol cars in an effort to pursue, detain and ticket or warn those persons who they observe to have violated the traffic laws Typically, an officer will monitor vehicle velocity by using a wide variety of alternative means to monitor such velocity, including the use of a radar gun (e.g., a Doppler radar), a laser beam, or sensing coils or pads placed on the roadway, as in U S Pat No 4,234,923 These alternative means require the involvement of at least one police officer, and a patrol vehicle including all equipment normally supplied a patrol vehicle These resources are costly and are of limited supply Further, the step of pursuing and detaining traffic ordinance violators can be dangerous to the police officer and the public at large. For example, an irate driver threatens the officer, the driver makes an effort to evade the officer, initiating a high speed chase, or the driver pulls over in an unsafe area on the highway, thus subjecting others to an unnecessary danger of collision

Despite the dangers associated with the current methods of traffic ordinance enforcement, the benefits obtained outweigh the costs and dangers to the public Proper enforcement results in the reduction in the number of traffic accidents and traffic fatalities, and a decrease in the costs to society of medical treatment and automotive and medical insurance This was observed to have been the case when the national speed limit on interstate highways was reduced from 70 mph to 55 mph. In addition, the reduction of traffic accidents is highly correlated with a reduction in traffic congestion When a patrol vehicle blocks even just one lane of a multi-lane highway, this may disproportionately decrease traffic through-flow due to the need of accommodating merging traffic and due to a phenomenon commonly known as "rubber-necking" (the tendency of persons who notice an accident or accident scene to slow down in order to better observe the accident scene).

Traffic enforcement devices, which provide a means for enforcement of the traffic ordinances without the direct involvement of a police officer or a patrol vehicle, have been in use for some time in Europe and in other regions of the world U.S Pat Nos. 4,866,438 and 5,066,950 describe remotely located devices which include a radar device and means of automatically triggering a high resolution photographic camera when a vehicle passes within its field of detection. These systems require matching of the license plate number read from a photograph taken by the camera with a number in a

database of registered vehicles in the state, region or nation. Upon identification, a traffic citation is issued and mailed to the registered owner of the vehicle in a non-confrontational manner without utilizing a patrol vehicle or a police officer's time. Despite these advantages, because the location of the violation must be noted on the citation (if it is not readily apparent from the photograph taken by the device) and is almost always supplied to the driver, the public may soon become aware of the location of the devices. When this occurs, drivers will know that they must slow down at this location in order to avoid receiving a traffic citation. Although slowing traffic to safe limits is a purpose of these prior art devices, this purpose will only partly be accomplished (i.e., persons will obey the traffic ordinances within the field of detection of the device). An effective system of such devices, capable of enforcing the traffic ordinances within an entire urban area, will be prohibitively expensive, because the urban area which is to be monitored must have a sufficient number of these units to ensure that a majority of the streets in the area are, in fact, being monitored (i.e., in order to minimize or eliminate any streets on which drivers having knowledge of each enforcement unit location can violate the traffic ordinances with impunity). Using only conventional technology, this mandates that an effective system of enforcement be comprised of a large number of these units which essentially blanket the urban area. Because each unit consists of relatively expensive and technologically sophisticated components, a system which blankets all drivable streets and highways is prohibitively expensive.

Therefore, what is needed is a system which enables effective, low cost enforcement of traffic ordinances without requiring that a police officer and patrol vehicle pursue and detain suspected traffic ordinance violators. Further, what is needed is a system which cannot be defeated by radar jamming or by the driver merely slowing down within range of an enforcement unit.

Summary of the Invention

The foregoing problems are solved and a technical advantage is achieved by the provision of a traffic law enforcement system having two or more enforcement units and at least one central computer connected via network devices. The enforcement units are spaced apart a given distance and each has a license plate reader. The central computer receives inputs from the enforcement units. The enforcement units and the central computer cooperate to calculate an average velocity of a vehicle which passes between enforcement units by using the inputs of a) drivable distance between enforcement units which transmitted matching license plate numbers, b) posted speed limit data between enforcement units which transmitted matching license plate numbers, and c) time lapsed between the transmission of the matching license plate numbers to the central computer.

In another feature of the invention, a signal is sent to the enforcement unit which was last in time to send the matching license plate number. The signal causes the enforcement unit to capture and store evidentiary data (e.g., an image) of the vehicle having the matching license plate number for enforcement purposes.

In another feature of the invention, the system may include more that two enforcement units which cooperate with each other and the central computer to identify a vehicle whose average velocity is calculated across paths between at least three enforcement units This permits the capture of at least two images of the vehicle for evidentiary purposes

An advantage achieved with the present invention is that a system is provided which enables effective, low cost enforcement of traffic ordinances without requiring that a police officer and patrol vehicle pursue and detain suspected traffic ordinance violators.

Another advantage of the present invention is that vehicles associated with wanted persons may be identified and the police department may be subsequently notified

Another advantage of the present invention is that the time in which the license plate numbers are held in a database need only be a short period. This is due to the fact that only those vehicles which quickly pass through or within an urban area generate an average velocity calculation which exceeds the posted limits between the two points Thus, all license plate data may automatically be erased after only a few minutes This will enable privacy concerns to be considered while, at the same time, maintaining an effective enforcement system.

Another advantage of the present invention is that enforcement units need only be placed on the outskirts of opposite ends of a city, thus only measuring the speed, and potentially ticketing those vehicles whose drivers use the city's roads, but do not pay city taxes This permits a more politically acceptable application of the system for enforcement purposes.

Still another advantage is that decoy units may be randomly replaced with enforcement units and vice versa, thus permitting the system to provide a deterrent effect while simplifying the system by mixing simply constructed decoy units with more complicated enforcement units

Brief Description of the Drawings

Other objects and advantages of this invention will become readily apparent as the same is better understood by reference to the following detailed description when considered in connection with the accompanying drawings wherein:

Fig 1 is a landscape view showing the basic components of the system of the present invention.

Fig 2a is a perspective view of an enforcement unit and a mounting structure of the system of the present invention

Fig 2b is a perspective view of an alternate embodiment of the mounting structure of the system of the present invention

Fig 3 is a perspective view of either an enforcement unit or a decoy unit of the present invention

Fig 4a is a schematic view of an enforcement unit of the present invention

Fig 4b is a schematic view of the system of the present invention.

Fig. 5 is a flow diagram of a summary method of the present invention

F: ; 6 is a representative map of a metropolitan area showing the locations of five enforcement units.

F' ; 7 is a lookup table used in the system of the present invention.

F ; 8 is a flowchart of the method of the present invention.

)etailed Description of the Preferred Embodiment

Now referring to Fig 1, in which is shown a preferred embodiment of the system of the present i vention. the traffic law enforcement system **18** includes at least two enforcement units **20**, optional d coy units **22** (shown in Fig. **3**). and a receiving interface **24** onto which either the enforcement unit or a y decoy unit **22** may be engaged

In order to permit identification of a potential violator, identifying indicia **82** is placed on a v sible portion of an automobile **80**. such indicia including a conventional license plate number, i spection sticker. registration sticker, or alphanumeric symbols placed on the surface of the automobile) which the characters are large enough to be read by a Number Plate Recognition (described in more d tail below).

The vehicle speed determination and evidence capturing capability of the traffic law enforcement s stem **18**. combined with the fact that motor vehicles **80** for use on freeways **90** have identifying l cense plates **92** with alphanumeric symbols of a size sufficient to be captured in a legible form, n ables remote enforcement of the speed limits by ticketing or warning the registered owner of any v chicle found to have exceeded the posted speed limits

Now referring to Fig 2a. 2b. and 3. the enforcement unit **20** includes a mating interface **36**. hown in dashed lines. a housing **100** and a multi-functional license Number Plate Recognition device "NRD") **30'** The receiving interface **24a** includes a mounting portion **32** and an interface end **34** hich releasably engages with the mating interface **36** on the enforcement units **20** or the decoy unit **22** The mounting portion **32** is specially fabricated to interface with and securely mount to a structure **40**, djacent to or above a highway or street, using a locking device **43** to prevent tampering The receiving nterface **24a** and an alternate interface **24b** enables secure, precise and repeatable attachment of an nforcement unit **20** or decoy unit **22** to various types of structures, such as a concrete railing, a idewall of an overpass, or a dedicated support structure. A power and/or communications junction box 45. and corresponding cable conduit **47** attach to the structure **40** A power and/or communications able **49** connects to the junction box **45**

The receiving interface **24a** and the mating interface **36**. enable routine relocation of the nforcement unit **20** to other geographic locations, and/or the substitution of a simply constructed decoy nit **22** in the place of the enforcement unit. thus increasing the difficulty of a driver discriminating between active enforcement units and decoy units, decreasing the number of relatively complicated ctive enforcement units required in the system (by substituting most of them for simply constructed decoy units). and, consequently. decreasing the complexity and cost of the entire system **18**.

In another configuration, the receiving interface **24a** or **24b** includes a mounting frame **42** w ich is permanently affixed to the structure **40** using conventional fastening devices, such as bolts **44**. In the alternate configuration of the receiving interface **24b**, the mounting portion **32** has the form of a h nger having a clamping end **46** which affixes to a highway structure **40**, and an interface end **34** w ich releasably engages with either the enforcement **20** or decoy unit **22**.

The housing **100** of the enforcement unit **20** further includes a panoramic portal **154** extending th ough an arc on the housing, the arc being of an angular magnitude sufficient to enable the retargeting o the video camera **26** within a range of angular increments which permit easy adjustment of the ta geting of the camera In case of a multi-lane highway or thoroughfare **90**, an enforcement unit **20** is d dicated to each lane of the highway or street in order to minimize the possibility of a driver avoiding th e enforcement unit. Thus, if there are three lanes to the highway **90**, all lanes directing traffic in a s ngle direction, three enforcement units **20** are positioned over each lane. Such an arrangement further r duces the processing burden on each enforcement unit **20**

The wiper device **156** optionally mounts above the portal **154**. The wiper device **156** includes a moisture or water-activated sensor **160** which causes the wiper to wipe moisture from the portal **154** a predetermined intervals

The housing **100** further includes handles **162** mounted on the housing to facilitate the process o substituting enforcement units **20** for decoy units **22** and vice versa.

Optionally, built-in blowers **164** and a heater **166**, together with a thermostat and circuit **170** m ay be provided to avoid temperature extremes beyond the operational limits of the enforcement unit 2 0

A receiving dish **50** and a transmitting device **52** are affixed to the mounting frame **42** of the r ceiving interface **24a** via a stanchion **54** and a mounting gimbal assembly **56**, and are undisturbed w hen the enforcement unit **20** or the decoy unit **22** is removed from the receiving interface **24a**. This e mits one-time targeting of the receiver **50** and the transmitter **52** to its associated line-of-sight cell, h ub or router **60**. The subsequent interchange of enforcement units **20** does not disturb the targeting of th e receiver **50** or the transmitter **52**

Referring now to Fig 4a in which a schematic of an enforcement unit **20** of the present i vention is shown, the camera **26** is operably connected to the NRD **30'** The camera **26** and NRD **30'** a re enclosed within a housing **100** The camera **26** may be standard or include IR illumination **140**, as w ell as features such as a zoom lens **134** and the capability of taking high-resolution video images The N RD **30'** includes a video capture device ("VCD") **302** connected to a computing device (essentially a P C) which includes RAM memory **122** for image processing, a hard disk ("HD") **124** for image and d ata storage including storage of pattern recognition software **260** (alternately, an EPROM **260'** p rogrammed with the pattern recognition software may substitute for the hard disk), a CPU **127**, and a

network device **121**. The network device **121** (e.g., an RS232 serial port and dedicated data line, a modem, ethernet, radio or other wireless network device) capable of data transmission and reception, connects to the NRD **30'** to permit near real-time transmission of signals to and from a central computer **350** (shown in Fig. **4b**) at a command station **220** (shown in Fig **4b**). An NRD **30'**, suitable for this application, is available from such companies as Monitron International of Worcestershire, England. Under ideal conditions, the Monitron NRD **30'** is able to reliably identify license plates on vehicles traveling from 0 to 100 or more mph at a distance of 60 or more meters Further, the Monitron NRD **30'** can handle traffic flow rates in excess of 100 vehicles per minute and can identify a license plate in less than one half second However, performance of an NRD **30'** can be easily tailored to the needs of the application through the appropriate selection of the individual components to make a custom NRD.

Now referring to Fig **4b**, the system **18** of the invention is shown. Enforcement units **20** and, optionally, decoy units **22** are placed in strategic locations along traffic flow routes, typically within a metropolitan area **600** (shown in Fig **6**) The enforcement units **20** are connected via network lines **68** to a network device **254** The network device **254** connects to the central computer **350** at the command station **220** The enforcement units **20** transmit data in a data stream including license plate number data, time of transmission, and a location code in which the related data is separated by separators and unrelated data is separated by start bits

The central computer **350** within the command station **220** is an IBM compatible computer having at least a "PENTIUM II" 233, or better, 32 MB of RAM memory, and a hard disk with 4 GB of available storage Also, the central computer **350** is loaded with "WINDOWS" 3 11 or better 'WINDOWS 95" OR "WINDOWS NT" can be used), a specially modified version of the above or suitable substitute (such as a "UNIX DERIVED" operating system)

Referring again to Fig. **4a**, any images captured by the VCD **302** which were stored during the course of a day are transmitted across the communications path **68** between the command station **220** and the enforcement unit **20** at an appropriate time, such as during a period of low use or low noise (e.g., in the nighttime hours). Note that the capacity of the HD **124** can be maximized and the data transmission rate improved using JPEG image compression, for example. If the communications path **68** is a telephone line, then the image **108** may be transmitted via modem to the central computer **350**, the central computer using the corresponding network device **254** to answer and communicate with the computer device at the enforcement unit **20**. This enables real-time transmission of the lower resolution video image, and transmission of larger high-resolution image files during off-peak hours via a telephone line However, whenever the communications link permits, the transfer should take place immediately over the network line via a comlink

It should be understood that the communications path described in the embodiments above may be comprised of any of a number of different paths, including UHF/VHF, microwave, cable, network

l ne. telephone line. optical fiber, cellular wireless, ethernet, line-of-sight wireless, satellite, a laser link. c · powerlines.

Where closed-circuit communications cable (e.g., a fiber-optic computer networking cable) provides the communications path between the enforcement unit and the command station. simpler equipment can be used.

The infrared illuminator **140** provides powerful infrared lighting that is invisible to the human eye, yet visible to the video camera. thus enabling the capturing of infrared images of a moving vehicle at night or day without startling or disturbing the driver The illuminator **140** is mounted to the housing, and includes a built-in photocell which automatically turns the illuminator on at night and off at dawn Built-in blowers are also provided to keep the illuminator cool. A suitable illuminator. in wide-angle and narrow angle versions is. part no. HAS-7698A. and HAS-7698B, respectively, available from Home Automation Systems (URL: http //www.techmall com/smarthome/7690 html) or the P345 IR Illuminator Module from Pearpoint Inc. of Thousand Palms, California. In addition, the camera **26** may have an infrared filter.

In a summary of the method of operation of the invention, as shown in Fig 5. the traffic law enforcement system **18** executes four steps

In a first step **500**. the method gathers license plate number data and transmits such data to the central computer **350** The enforcement units **20** read license plate numbers from passing vehicles **80** at two or more locations and transmit the license plate numbers to the central computer **350**

In a second step **520**. the central computer **350** associates a time of the transmission from the enforcement units **20** to the central computer and a location of the source of the license plate number in a manner which enables the central computer to recognize when a license plate number is received which matches another license plate number received earlier in time and within a predetermined maximum time period. The central computer **350** then accesses a data lookup table **700** (shown in Fig 7) The table **700** includes i) in column 5, an estimation of a minimum drivable distance between the two locations, for example **X1** and **X2**. of the enforcement units **20** which sent the matching license plate numbers. and ii) in column 6. an estimation of the maximum average permissible velocity between the two locations. This estimation is generated. at least indirectly, from speed limit data corresponding to road segments (**612**, **614**. **616**, **618** and **620** shown in Fig. 6) which defined the minimum drivable distance between the at least two locations **X1** and **X2**.

In a third step **540**, the central computer **350** calculates the average velocity of the vehicle **80** between the two locations and compares the maximum average permissible velocity with the average velocity of the vehicle **80**

In a fourth step **560**. if the average speed of the vehicle exceeds by a predetermined margin the maximum average permissible velocity between the locations of the enforcement units **20**. evidentiary

in ormation is stored for future retrieval (e g . an image of the vehicle may optionally be captured for ev dentiary purposes)

Referring now to Fig 6, a representative map of a metropolitan area **600** is shown having five ei forcement units at locations **X1 X2, X3, X4** and **X5** placed throughout the area. Known paved si rfaces **610** such as highways, representing road segments **612, 614, 616, 618** and **620** between ei forcement units **20**, crisscross the metropolitan area **600**.

Referring now to Fig 7 in which is shown the lookup table **700**, in column 1 of the table is a li ting of all possible combinations of any two enforcement units **20** at locations **X1, X2, X3, X4**, and X 5 The shortest paved surface distances from one enforcement unit **20** to another is measured and s ored in the table **700** in column 5, in a row corresponding to the combination of the two enforcement u uts which transmitted the matching license plate numbers. In order to generate the data in column 6 c the table **700**, the segment lengths and posted speed limits along each segment **612, 614, 616, 618** a id **620** are noted in columns 2-4 for each segment. An average maximum permissible velocity ("AMV") is calculated by an appropriate means. One such means is through the use of the below f rmula:

$$AMV = \frac{Dt}{((D1/PS1) - (D2/PS2) + (D3/PS3) + \quad + (Dn/PSn))}$$

in velocity units such as mph, where:

AMV = average maximum permissible velocity between the two locations,

Dt = total distance between the two locations,

Dn = distance of the "nth" segment; and

PSn = the posted speed limit for the "nth" segment,

or empirically, using the following relationship

AMV = Dt/EMT, where

EMT = empirically measured time to drive the distance Dt, determined at maximu m posted speed limits and for a safe rate of acceleration

The average maximum permissible velocity AMV for every possible combination of enforcement unit ocation is recorded in column 6 of the table **700**, in the same row as the associated total distance and he combination of the two enforcement units which sent the matching license plate numbers

The method of the invention, shown in more detail in Fig. **8**, includes the following steps

In a first step **800**, data is gathered and transmitted to the central computer **350** for analysis This first step **800** is made up of three substeps In a first substep, using known license plate number

r cognition equipment and techniques (described in more detail above), enforcement units **20** routinely r ad license plates of passing vehicles **80**. whether or not they are exceeding the posted speed limit. In a second substep. the location, time. and a license plate number of each vehicle **80** is transmitted to the c ommand station **220** and stored in a license number database for a predetermined period of time. In a t ird substep, the license number database is scanned and all license plate number inputs having an a sociated time which has been in storage longer than the predetermined period of time are deleted from t e license number database This predetermined period of time need be only a few minutes (e g , 10 n inutes), due to the fact that only those vehicles **80** which pass quickly through or within a r etropolitan area **600** generate an average velocity calculation which exceeds the posted limits between t e locations of the enforcement un.ts **20** which sent the matching license plate number data

Note that when the predetermined time period mentioned above is short, data inputs are deleted r a short period. Publication to the general public that such data will be quickly erased from the l ense number database (unless a violation of the average maximum permissible velocity is exceeded b / a predetermined margin or the vehicle is believed to be a stolen vehicle or registered to a wanted f lon) will tend to satisfy concerns of persons that such gathered data might be permanently stored in c der for enforcement authorities to learn of the travel and driving habits of individual persons, in v olation of their rights of privacy. After this predetermined period passes, all license plate data may a tomatically be erased

In a second step **820**. the license number database is scanned for trigger information. This s cond step **820** is made up of three substeps. In a first substep. a subroutine operating on the central c mputer **350** at the command station **220** reads the input license plate numbers and continuously c mpares them with other license p.ate numbers previously received in the license number database. In a second substep. when the subroutine reads the same license plate number, the subroutine either p oceeds to the next substep or initiates the sending of a signal from the command station **220'** to the e forcement unit **20**, the signal causing the capture of evidence (such as an image) related to the vehicle **8**) In a third substep, the time and location data associated with the matching license plate numbers is a cessed

In a third step **840**, the average speed of the vehicle **80** is calculated The subroutine calculates t e time difference Td and accesses data in column 5 of the table **700** on the minimum paved distance D between the two enforcement units **20** which read the matching license plate numbers in order to c lculate an average velocity of the vehicle **80** associated with the license plates. This average velocity is subtracted from the average max mum permissible velocity ("AMV") obtained from column 6 of the t ble **700** The following formula may be used:

$$EV = ((Dt/Td) - AMV) \text{ in velocity units}$$

where

EV is velocity in excess of the AMV.

Negative values of AMV are ignored as such represent a vehicle traveling less than the AMV

In a fourth step **860**, in the event of a violation of the traffic ordinances, evidentiary data is gathered to support subsequent ticketing or a warning notice. This fourth step **860** includes four substeps. In a first substep, if this average velocity exceeds the average velocity of a hypothetical vehicle **80** passing along the shortest paved path between the enforcement units **20**, then the command station **220** immediately sends a signal along a communications path **68** to the enforcement unit **20** which sent the most recent signal, instructing the computer device in the enforcement unit to capture the image of the vehicle (if this has not already been done) and to either store the image on the HD **124** of the computing device in the enforcement unit for later retrieval, or to immediately transmit the captured image of the vehicle **80** to the central computer **350** for storage there

The output which would be obtained is used to support any subsequently issued ticket or warning letter Such output might contain the following information:

time of violation \ license plate number \ speed in excess of AMV \ AMV

Of course, this information would likely best be provided with an attached video image clearly showing the face of the driver

Note that the image could optionally be captured on the central computer **350** at the command station **220'**, were the video image transmitted real time to the central computer, thus eliminating the need of a NRD **30'** in each enforcement unit **20**. Note also that no image need be captured at all It may be politically more acceptable to rely purely on the evidentiary value of a print out of the license number and associated data because such may be less likely to violate the privacy interests of drivers In a second substep of the fourth step **860**, the image, if captured, may be stored on the hard disk (not shown) of the central computer **350** for use in subsequent ticketing or to support a warning Such image may also be stored in the HD **124'** of the computer device in the enforcement unit **20** and then, at a more convenient time, transferred via modem, for example, to the command station **220**. In third substep, the earlier transmitted license plate number and associated data (such as location and time of transmission) are deleted from the license number database and the enforcement unit **20** injects a new signal into the data stream of license plate numbers and associated data being transmitted to the central computer **350** This new signal is stored in the license number database which includes the license plate number, an associated location and a new time, together with a flag associating the data with the recently stored or captured evidentiary data (such as a captured image) The flag may constitute the file name of the captured and stored video image Such evidentiary data, including associated data such as time, location and license number, constitutes the flagged data as referred to hereinafter

In a fourth substep, when the central computer **350** recognizes another license plate number match with the flagged data, the match resulting from data sent from a third enforcement unit **20**, then the method returns to the third step **840**, and continues as described above However, if a velocity associated with the flagged data exceeds the AMV between the two locations by a predetermined amount, any resulting second set of evidentiary data (e g . an image) is stored in association with the earlier captured evidentiary data such that an operator can easily locate and associate the data for enforcement purposes In addition, enforcement authorities now can choose which violation they would prefer to prosecute the registrant of the vehicle **80** for, depending on the quality of the captured evidentiary data and the excess velocity of the vehicle at the time of capture Enforcement authorities and the public may prefer enforcement based on the second set of captured evidentiary data (particularly when such data includes images) and calculated average speed because of the better evidentiary quality of being able to associate the captured images at each time and location measuring point This increases the likelihood that any resulting ticket will be legally enforceable.

In another embodiment of the invention, shown as step **510** in Fig 5, the license plate data in the license number database is compared with license numbers in a wanted-vehicle database (not shown) The license numbers in the wanted-vehicle database are of vehicles which enforcement authorities have previously identified as vehicles of interest for further investigation When a match is found, the license number and time and location data are sent to enforcement authorities for further action It is desirable in such instances that a match trigger an alarm in order to improve the response time of enforcement authorities. Such may be accomplished by using a dial-back on alarm condition feature, available from Monitron International of Worcestershire. England

In an advantage of the invention, the measuring of an average velocity between relatively distant points discourages acceleration of a vehicle **80** between enforcement units **20**, and then slowing down when a driver of the vehicle believes he is within their enforcement range. Thus drivers of vehicles **80** are less likely to be able to defeat the traffic law enforcement system **18** of the invention

An advantage achieved with the present invention is that a system is provided which enables effective, low cost enforcement of traffic ordinances without requiring that a police officer and patrol vehicle pursue and detain suspected traffic ordinance violators.

Another advantage of the present invention is that vehicles **80** associated with wanted persons may be identified and the enforcement authorities, such as the police department, may be subsequently notified

Another advantage of the present invention is that the time in which the identifying indicia **82** is held in storage need only be a short period. This will enable privacy concerns to be considered while, at the same time, maintaining an effective enforcement system **18**

Another advantage of the present invention is that enforcement units **20** may be placed only on the outskirts of opposite ends of a city, thus only measuring the speed, and potentially ticketing those

vehicles which use the city's roads, but do not pay city taxes. This permits a more politically acceptable application of the system **18** because it helps ensure that those who use the city's roads indirectly pay their share of the costs of maintaining such roads

Another advantage is that decoy units **22** may be randomly replaced with enforcement units **20** and vice versa, thus permitting the system **18** to provide a deterrent effect while simplifying the system through mixing simply constructed decoy units with more complicated enforcement units

Although illustrative embodiments of the invention have been shown and described, a wide range of modification, changes and substitution is contemplated in the foregoing disclosure In some instances, some features of the present invention may be employed without a corresponding use of the other features Accordingly, it is appropriate that the appended claims be construed broadly and in a manner consistent with the scope of the invention.

Industrial Applicability

The invention is applicable industrially as a means of reducing the velocity of drivers to safe limits while enabling more effective and safer enforcement of the traffic ordinances (by requiring less police interaction and the dedication of fewer police resources, such as police cars and related enforcement equipment) Such a system should play an important role in permitting municipalities to dedicate police resources to the enforcement of more serious criminal laws, or, alternately, to reduce the municipalities' traffic law enforcement costs

What is claimed is:

1 A traffic law enforcement system wherein

at least two enforcement units having license plate readers are spaced apart a given distance,

at least one central computer receives inputs, including license plate numbers of vehicles which pass the license plate readers, from the at least two enforcement units; and

the at least two enforcement units and the at least one central computer cooperate to calculate an average velocity of a vehicle which passes between the at least two enforcement units, using the inputs of a) drivable distance between enforcement units which transmitted matching license plate numbers, b) posted speed limit data between enforcement units which transmitted matching license plate numbers, and c) time lapsed between the transmission of the matching license plate numbers to the central computer

2 The system of claim 1 further comprising at least one decoy unit and attachment means which enable an enforcement unit to be replaced by a decoy unit and vice versa

3 A traffic law enforcement system having at least two enforcement units at at least two locations and a central computer, wherein

the at least two enforcement units read identifying indicia from passing vehicles at the at least two locations and transmit at least the identifying indicia to the central computer, and

wherein

the central computer

a) associates a time of the transmission and a location of the source of the identifying indicia such that when the central computer recognizes that an identifying indicia was received which matches another identifying indicia received earlier in time and within a predetermined maximum time period, the central computer accesses a table, the table including

i) an estimation of a minimum drivable distance between the at least two enforcement units which sent the matching identifying indicia and,

ii) an estimation of the maximum average permissible velocity between the two locations the estimation generated, at least indirectly, from speed limit data corresponding to road segments which defined the minimum drivable distance between the at least two locations,

b) calculates the average speed of an alleged vehicle which passed between the at least two locations; and

c) compares the maximum average permissible velocity with the average velocity of the vehicle for the purpose of determining whether the vehicle exceeded the maximum average permissible velocity between the at least two locations.

4 The system of claim 3 further comprising at least one decoy unit and attachment means which enable an enforcement unit to be replaced by a decoy unit and vice versa

5 The system of claim 3, wherein a signal is sent to the enforcement unit which was last in time to send matching identifying indicia to cause the enforcement unit to capture an image of the vehicle having the matching identifying indicia for enforcement purposes.

6 The system of claim 1, wherein at least three enforcement units cooperate with the at least one central computer to identify a vehicle whose average velocity is calculated across the path of the at least three enforcement units and in which at least two images of the vehicle are recorded for evidentiary purposes

CIP

Attorney Docket No 777

TRAFFIC LAW ENFORCEMENT SYSTEM

Abstract of the Disclosure

A traffic law enforcement system having two or more enforcement units and at least one central computer connected via network devices. The enforcement units are spaced apart a given distance and each have a license plate reader The central computer receives inputs from the enforcement units, including license plate numbers of passing vehicles. The enforcement units and the central computer cooperate to calculate an average velocity of a vehicle which passes between enforcement units by using the inputs of a) drivable distance between enforcement units which transmitted matching license plate numbers, b) posted speed limit data between enforcement units which transmitted matching license plate numbers, and c) time lapsed between the transmission of the matching license plate numbers to the central computer



Fig. 1


45
162
162
162
36
140
122
50
52
100
156
26
30
154
20
152
56
54
34
46
40
246
42
24a
32
44
45
47
54
34

Fig. 2a

Fig. 2b



Fig. 3



Fig. 4a



Fig. 4b


LICENSE PLATE NO. DATA IS GATHERED AND TRANSMITTED TO A CENTRAL COMPUTER
501
OPTIONALLY COMPARE DATA WITH WANTED-VEHICLE DATABASE; IF A MATCH, ACTIVATE ALARM
510
THE CENTRAL COMPUTER STORES THIS DATA, ASSOCIATES IT WITH THE SOURCE LOCATION AND TIME OF TRANSMISSION OF THE DATA, AND COMPARES THE DATA
520
WHEN A MATCH OF LICENSE PLATE NUMBERS IS FOUND, THE CENTRAL COMPUTER CALCULATES AN AVERAGE SPEED OF A VEHICLE
540
IF THE CALCULATED AVERAGE SPEED EXCEEDS THE MAXIMUM AVERAGE PERMISSIBLE SPEED BY A PREDETERMINED MARGIN, EVIDENTIARY DATA IS GATHERED FOR TICKETING OR WARNING PURPOSES
560

Fig. 5



600

Fig. 6

Table

Comb.	Seg. no.\ dist. miles	speed limit in seg.	Seg. no.\ dist. miles	speed limit in seg.	Seg. no.\, dist. miles	speed limit in seg.	Dt miles	AMV (mph)
1-X2	612\2	55					2	55
1-X3	612\2	55	614\3	45			5	48.5
1-X4	612\2	55	614\3	45	616\2	30	7	41.7
1-X5	620\3	10					3	10
2-X3	614\3	45					3	45
2-X4	614\3	45	616\2	30			5	37.6
2-X5	612\2	55	620\3	10			5	14.9
3-X4	616\2	30					2	30
3-X5	616\2	30	618\4	45			6	39
4-X5	618\4	45					4	45

700

Fig. 7



Fig. 8

United States Patent & Trademark Office

Office of Initial Patent Examination -- Scanning Division



Application deficiencies found during scanning:

1 Application papers are not suitable for scanning and are not in compliance with 37 CFR 1.52 because

- ☐ All sheets must be the same size and either A4 (21 cm x 29.7 cm) or 8-1/2"x 11" Pages _____ do not meet these requirements.
- ☐ Papers are not flexible, strong, smooth, non-shiny, durable, and white.
- ☐ Papers are not typewritten or mechanically printed in permanent ink on one side.
- ☐ Papers contain improper margins. Each sheet must have a left margin of at least 2.5 cm (1") and top, bottom and right margins of at least 2.0 cm (3/4").
- ☐ Papers contain hand lettering.

2 Drawings are not in compliance and were not scanned because:

- ☐ The drawings or copy of drawings are not suitable for electronic reproduction.
- ☐ All drawings sheets are not the same size. Pages must be either A4 (21 cm x 29.7 cm) or 8-1/2" x 11"
- ☐ Each sheet must include a top and left margin of at least 2.5 cm (1"), a right margin of at least 1.5 cm (9/16") and a bottom margin of at least 1.0 cm (3/8").

3 Page(s)_____ are not of sufficient clarity, contrast and quality for electronic reproduction

4 Page(s)_____ are missing.

5 OTHER NO DECLARATION